59.00 EUR
incl. 19% VAT, plus shipping

- GPS/GSM/UMTS/3G !
- WLAN / Bluetooth !
- Active antenna !
- SMA connectors !

Support: Specifications

Combined Roof mount antenna for Fleet management systems, Navigation, Telematics applications in association with WLAN. AMPS, GSM, GPS, Glonass,DCS, PCS, 3G, WiFi and Bluetooth.

3x SMA male, 3m.

GSM/UMTS Specifications
Frequency range: 900 Mhz (GSM 850/900)
Gain: 2.2 dBi
VSWR: <3:1
Polarization: Vertical
Impedance: 50 ohm

GPS Specifications
Center frequency: 1575.42 MHz
Power gain: 26dB at 3V, 27dB at 5V dB
Noise figure: 1.15 -dB
Polarization: RHCP

VSWR: <1.2:1
Impedance: 50 ohm
Supply voltage: 2.7 - 5.5 V
Current: 15 - 25 mA

W-LAN/BT Specifications
Frequency: 2.4 GHz
Gain: 2 dBi
VSWR: < 2.1
Polarization: vertical
Impedance: 50 ohm

Basic Informations
Size: 64mm x 98mm x 59.5mm
Temperature: -40 to 85 °C
Cable length: 3m
Cable type: RG174U
Con GSM: SMA Male
Con GPS: SMA Male
Con WiFi: SMA Male
Mounting hole: Square (15 x15 mm)