

189.00 EUR

incl. 19% VAT, plus [shipping](#)

- 7x USB 3.0 !
- ESD / 350W !
- 3.2 GEN 1 / 5Gbit/s !
- Industriequalität !



#### RUGGED AND RELIABLE:

With a metal housing, air/contact ESD protection up to 15 kV/8 kV, and 350 W surge protection, this robust USB 3.2 Gen 1 hub reliably connects 7 USB devices in harsh industrial environments. **MOUNTING OPTIONS:**

This USB hub can be securely installed on/under a desk, on a wall, or on a DIN rail using the integrated mounting lugs and included DIN brackets. A 1.8 m USB 3.2 Gen 1 cable is included.

#### FLEXIBLE POWER SUPPLY:

For individual power requirements, the USB 3.2 Gen 1 hub supports a DC range of +7-48 V, power supply via DC dropout voltage, LPS with terminal block, or via a wall outlet using the included power adapter.

#### CHARGING AND POWERING:

This USB 3.2 Gen 1 (5Gbps) hub provides a total of 35 W to power all downstream devices and supports BC 1.2, which delivers up to 2.4 A (12 W) to any two ports, depending on the available power.

#### THE IT PROFESSIONAL'S PREFERRED CHOICE:

Designed and built for computer professionals, this USB hub is supported for 2 years, including free lifetime multilingual technical support. (24/5)

|                         |                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------|
| <b>Model</b>            | <b>HB30A7AME</b>                                                                                 |
| LED-Anzeiger            | 1 - Stromversorgung (Grün)<br>7x USB 3.2 Type-A (9 pin, Gen 1, 5Gbps)                            |
| Ports                   | 1x USB 3.2 Typ-B (9-polig, Gen 1, 5Gbit/s)<br>1x Klemmleiste (2 Drähte)                          |
| Schnittstelle / Bus Typ | USB 3.2 Gen 1 (5Gbit/s)                                                                          |
| Industrienormen         | USB-Akkuladespezifikation Rev. 1.2<br>USB 3.2 Gen 1 - abwärtskompatibel mit USB 3.0, 2.0 und 1.1 |
| Chipset-ID              | Genesys Logic - GL3523                                                                           |
| ESD Protection          | +/-15kV (Air)<br>+/-8kV (Contact)                                                                |
| Überspannungsschutz     | 350 W an DFP und UFP                                                                             |
| MTBF                    | 126.106 Stunden                                                                                  |
| Stromversorgung         | AC Netzadapter19,5V DC 65W<br>Klemmleiste (2 Drähte)<br>0°C to 70°C (32°F to 158°F)              |
| Betriebstemperatur      | Storage: -20°C to 85°C (-4°F to 185°F)<br>5 bis 95% relative Luftfeuchtigkeit                    |
| Abmessungen             | 14,5 x 5,5 x 4,5 cm<br>326g<br>1x USB Hub<br>1x USB 3.0 Hostkabel                                |
| Lieferumfang            | 1x Stromadapter EU<br>2x DIN Schienenklammern<br>4x Montageschrauben<br>1x Kurzanleitung         |